

Declaration of Performance

DOP-SCS9000-01

SCS9000 Silpruf NB

Silicone sealant

1.	Product Type Unique identification code of the product-type:	SCS9000 Silpruf NB
2.	Type, batch or serial number allowing identification of the construction product as required under Article 11(4):	SCS9000 Silpruf NB batch number on packaging
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Sealant for non-structural use in joints in buildings: façade elements, glazing. Type F EXT-INT CC - Class 25 LM & Type G CC - Class 25 LM
4.	Name and contact address of manufacturer as required pursuant to Article 11(5):	Momentive Performance Materials Silicones B.V. Plasticslaan 1 4612PX Bergen op Zoom, The Netherlands
5.	Authorized representative's name and address	Not applicable
6.	System(s) of assessment and verification of constancy of performance of the construction product as set out in the CPR, Annex V:	System 3
7.	Harmonized standard and Notified Body in case the declaration of performance is concerning a construction product covered by a harmonized standard (hEN)	EN15651-1 & 2 Notified body 0074
8.	European Technical Assessment and Notified Body in case the declaration of performance is concerning a construction product for which a European Technical Assessment has been issued:	Not applicable

GE is a registered trademark of General Electric Company and is under license by Momentive Performance Materials Inc. Momentive Performance Materials provides versatile materials as the starting point for its creative approach to ideas that help enable new developments across hundreds of industrial and consumer applications. We are helping customers solve product, process, and performance problems; our silanes, fluids, elastomers, sealants, resins, adhesives, urethane additives, and other specialty products are delivering innovation in everything from car engines to biomedical devices. From helping to develop safer tires and keeping electronics cooler, to improving the feel of lipstick and ensuring the reliability of adhesives, our technologies and enabling solutions are at the frontline of innovation.



Licensed Products



Declaration of Performance **SCS9000 Silpruf NB**

9. Declared performance

Essential characteristics	Performance	hEN or ETA
Reaction to fire	Class E	
Release of chemicals dangerous to the environment and health	See MSDS	
WATER AND AIR TIGHTNESS		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	EN15651-1 & 2
Tensile properties	NF	
Microbiological growth	Not applicable	
Elastic recovery	≥ 70% (F); ≥ 60% (G)	
Durability	Pass	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Name and function:

Place and date of issue:

Signature

Pepijn van Iersel, Product Manager Sealants EMBAI

Bergen op Zoom, Netherlands, May 27th, 2014

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC., MOMENTIVE PERFORMANCE MATERIALS USA INC., MOMENTIVE PERFORMANCE MATERIALS ASIA PACIFIC PTE. LTD., MOMENTIVE PERFORMANCE MATERIALS WORLDWIDE INC., MOMENTIVE PERFORMANCE MATERIALS GRAPH, THEIR SUBSIDIARIES AND AFFILIATES DOING BUSINESS IN LOCAL JURISDICTIONS (collectively "Suppliers"), ARE SOLD BY THE RESPECTIVE LEGAL ENTITY OF THE SUPPLIER SUBJECT TO SUPPLIERS STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTION OF OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOROMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIERS MAKE NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING SUPPLIERS' PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. AFOREMENTIONED EXCLUSIONS OR LIMITATION OF LIABILITY ARE NOT APPLICABLE TO THE EXTENT THAT THE END-USE CONDITIONS AND/OR INCORPORATION CONDITIONS CORRESPOND TO THE RECOMMENDED CONDITIONS OF USE AND/OR OF INCORPORATION AS DESCRIBED BY SUPPLIER IN ITS PRODUCT DATA SHEET AND/OR PRODUCT SPECIFICATIONS. EXCEPT AS PROVIDED IN SUPPLIERS' STANDARD CONDITIONS OF SALE, SUPPLIERS AND THEIR REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Suppliers' materials, services, recommendations, or advice for its own particular use. Each user must identify a perform all tests and analyses necessary to assure that its finished parts incorporating Suppliers' products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this periorii ai teste si alu airasyses incessary to assure unta its liminateu parts incorporating suppliers products, inacticais, or services will be said and airaspecial control to the united before the solid alter, vary, supersede, or waive any provision of Suppliers' Standard Conditions of Sale or this Disciolaimer, unless any such modification is specifically agreed to in a writing signed by Suppliers. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Suppliers or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

*SilPruf. SilShield, UltraGlaze and UltraSpan are trademarks of Momentive Performance Materials Inc. GE is a registered trademark of General Electric Momentive is a trademark of Momentive Performance Materials Holdings LLC. Copyright 2014 Momentive Performance Materials Inc. All rights reserved.

DOP-SCS9000-01 (1/06/2014)



CE Marking Information

(€	
0074		
Momentive Performance Materials		
14		
DOP-SCS9000-01		
EN15651-1 & 2		
Non-structural sealants for use in façade elements and glazing joints		
Type F EXT-INT CC - Class 25 LM & Type G CC - Class 25 LM		
Conditioning: Method A		
Substrate: Glass without primer, Aluminium without primer & Concrete with primer SS4179		
REACTION TO FIRE	Class E	
RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH	See MSDS	
WATER TIGHTNESS AND AIR TIGHTNESS		
Resistance to flow	≤3 mm	
Loss of volume	≤ 10%	
Tensile properties ie elongation after immersion in water at 23°C	NF	
Elastic Recovery	≥ 70% (F); ≥ 60% (G)	
DURABILITY	Pass	

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC., MOMENTIVE PERFORMANCE MATERIALS USA INC., MOMENTIVE PERFORMANCE MATERIALS ASIA PACIFIC PTE. LTD., MOMENTIVE PERFORMANCE MATERIALS WORLDWIDE INC., MOMENTIVE PERFORMANCE MATERIALS GMBH, THEIR SUBSIDIARIES AND AFFILIATES DOING BUSINESS IN LOCAL JURISDICTIONS (COILECTIVELY "SUPPLIERS"), ARE SOLD BY THE RESPECTIVE LEGAL ENTITY OF THE SUPPLIER SUBJECT TO SUPPLIERS" STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIERS MAKE NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING SUPPLIERS" PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. AFOREMENTIONED EXCLUSIONS OR LIMITATION OF LIABILITY ARE NOT APPLICABLE TO THE EXTENT THAT THE END-USE CONDITIONS AND/OR INCORPORATION CONDITIONS CORRESPOND TO THE RECOMMENDED CONDITIONS OF USE AND/OR OF INCORPORATION AS DESCRIBED BY SUPPLIER IN ITS PRODUCT DATA SHEET AND/OR PRODUCT SPECIFICATIONS. EXCEPT AS PROVIDED IN SUPPLIERS' DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Suppliers' materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Suppliers' products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Suppliers' Standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Suppliers. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Suppliers or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.



Licensed Products

CE-01 (1/06/2014)